

## CASE STUDY

### Ecofil70

Application: Fill material used in construction of new lorry park at Wissington sugar factory

#### Background

Anticipated increases in sugar product movements from British Sugar's Wissington Sugar Factory, near King's Lynn in West Norfolk necessitated the development of a new concrete lorry park with integral LGV washing facilities.

The project was planned and tendered for during spring 2006 and the design was initially based on the construction of the concrete pavement on a granular sub-base above a geotextile membrane.

Groundwork commenced in the summer, but the peaty nature of the soil demanded a rapid change in construction to counter the likely settlement of the pavement in service.

#### Sub-base and pavement construction

##### 1. Placement of Ecofil70

The peaty soil was removed to a typical depth of 900mm to the underlying clay.

A starter layer of coarse stone rejects was laid to a depth of 400mm and was then overlain with 300 to 400mm of Ecofil70.

The Ecofil70 was placed in 150mm layers and compacted using 4 - 6 passes of a 3 tonne self-propelled vibratory roller.



*Continued overleaf*

For more information, contact our Helpdesk:

**0870 240 2314** or visit [limex.co.uk](http://limex.co.uk)

## **2. Compaction of Ecofil70**

The fine nature of Ecofil70 ensured that levelling and profiling was straightforward.

The immediate strength of Ecofil70 meant that the shallow trenches necessary for drainage and utilities were easily dug and self-supporting with little break-over.



## **3. Application of crushed granite**

The Ecofil70 was finished with a 50mm compacted layer of crushed granite to minimise drying and dusting.



*Continued overleaf*

For more information, contact our Helpdesk:  
**0870 240 2314** or visit **limex.co.uk**

**LIMEX**

#### ***4. Construction of the pad***

Reinforced concrete was then laid at a depth of 225mm in 5 x 25 bays.



#### ***5. Lorry park in use.***

Since completion in September 2006 the lorry park has been subject to intensive trafficking without problems.

British Sugar plan to repeat the use of Ecofil70 as a pavement foundation material in future site projects following this successful product application.



For more information, contact our Helpdesk:

**0870 240 2314** or visit **[limex.co.uk](http://limex.co.uk)**

**LIMEX**